

# SAPPHIRE® PLUS



## SAPPHIRE PLUS suppression systems

FIREATER SAPHIRE® Fire Suppression Systems delivering 3M™ Novec™ 1230 Fire Protection Fluid is a safe, environmentally friendly clean agent that instantly vaporizes upon discharge, absorbing heat and providing total flooding of protected spaces.

### 70 Bar NOW Available!

SAPPHIRE Plus is a 70 bar system, which helps reduce the footprint, installation and service time by offering higher fill densities up to 1.4kg/L to reduce the number of containers. The increased pressure also permits the containers to be located much further from the protected space and increases the ability to introduce selector valves to protect multiple hazards from a single container bank. Additionally pipe sizes may be reduced increasing the economy and design flexibility.

The system benefits from new software, designed to maximise the benefits of the SAPHIRE Plus system.

The SAPHIRE system has a proven track record for protecting people, the environment and high value assets. Protect these assets with a SAPHIRE clean agent system, custom engineered to quickly suppress fires without causing harm and where clean-up of other agents poses a problem.



SAPPHIRE Plus Gaseous  
Fire Suppression Systems  
Delivering 3M™ Novec™  
1230 Fire Protection Fluid

- 70 Bar System
- Higher Fill Densities (up to 1.4 Kg/L)
- Reduced Footprint, Installation Cost and Service Time
- Extended Temperature Range -18°C to 65°C (UL/FM)
- Selector Valves
- Extended Pipe Runs
- New Design Software
- Environmentally Friendly
- Safe for People
- Fast Acting
- Optimised Pipe Sizes
- DOT/TPED Containers
- Dual Approved UL/FM & CE Pressure Gauge or Contacted Pressure Gauge
- Easy Halocarbon Retrofit
- In-Built Placement Switch Within Electrical Actuator

# Choose a Revolutionary Fire Suppression System

## SAPPHIRE Applications

- Data Centres
- Electrical Switching Rooms
- Machinery Spaces
- Medical Facilities
- Heritage Sites
- Air Traffic Control
- Oil and Gas Facilities

3M™ Novec™ 1230 Fire Protection Fluid provides a wide safety margin because it is used at concentrations of only 4.5 to 5.9% by volume which is well below the maximum 10% concentration for safe exposure. The agent has zero ozone depletion potential (ODP) and with an atmospheric lifetime of between three and five days and a global warming potential of 1.0, it is the most environmentally friendly chemical clean agent.

Every SAPPHIRE installation carries a 20 year environmental warranty covering both the agent and the system hardware.

## Fast Acting Suppression

SAPPHIRE systems work fast, delivering the agent within 6 to 10 seconds, suppressing fires before they have the chance to spread. Most importantly when a fire is suppressed quickly, the result is less damage, lower refurbishment costs and reduced downtime.

## Multiple Levels of Protection

- Total Flooding of Hazard Areas
- No Damage to Valuable Assets
- Wide Range of Applications
- Effective on Class A, B and C Fires
- UL Listed
- FM Approved
- LPCB RedBook Listed

## System Recharging

As the 3M™ Novec™ 1230 Fire Protection Fluid is stored as a liquid at room temperature the agent may be transported in 300kg drums or 1100kg totes enabling the agent to be made available quickly through a network of approved recharge facilities.



# State-of-the-Art Detection and Control

- Addressable or Conventional Options
- Single and Multi-Hazard Agent Releasing Panels
- UL & ULC Listed and FM Approved Options
- CE Marked Option

Globally the SAPPHIRE system is controlled by state-of-the-art detection and control systems using conventional or addressable AUTOPULSE microprocessor, MzXe and FAST 2000 control panels with highly sensitive smoke, heat and flame detectors.

When fire is detected, the control systems will sound alarms, close doors, shut down equipment and release the fire suppression system. The system has manual pull stations and provides automatic detection 24 hours a day, 365 days per year.

## The Ultimate Fire Suppression Solution

The FIREATER brand promises a full range of quality fire protection solutions. Our extensive network of Authorized FIREATER Distributors provides factory trained professionals to serve our customers virtually anywhere in the world.



UL Listed / FM Approved System	X		X
VdS System Approvals	X	X	
UL listed / FM Approved Selector Valves			X
EN 12094 Approved Selector Valves	X	X	X
EN 12094 Component Approvals	X	X	X
Combined EN 12094 Component Approval / UL Listed / FM Approved System			X
Marine Approvals	X		
CSIRO Approval	X	X	
CNPP Approval	X		
CNBOP Approval	X	X	
GOST Approval	X	X	
BOMBA Approval	X		
LPCB Redbook Listed			X

## Global Offices

### Americas

One Stanton Street,  
Marinette,  
WI 54143-2542, USA  
Tel. +1 715 735 7411

### Europe

Burlingham House,  
Hewett Road,  
Great Yarmouth, UK, NR31 0NN  
Tel. +44 (0) 1493 440 500

### Middle East

Block D, Floor 3,  
Office Park Building #56,  
Internet City, Dubai,  
United Arab Emirates  
Tel. +971 4455 0700

### Asia-Pacific

2 Serangoon North Avenue 5,  
#07-01, Singapore 554911,  
Singapore  
Tel. +65 6557 4360

For more information, visit [www.SapphirePlus.com](http://www.SapphirePlus.com) or follow [@JCI\\_Buildings](https://twitter.com/JCI_Buildings) on Twitter.